

# Pine Oil 60%

Technical Data Sheet  
midhills

Latest Updated 1/07/2023

## REMARK

The above information is believed to be accurate and presents the best explanation currently available to us. We assume no liability resulting from above content. The technical standards are formulated and revised by customers requirements. If there are any changes the latest specification will be executed and confirmed in the contract.

**midhills**

# Pine Oil 60%

(CAS: 8002-09-3 EINECS: 304-455-9)

- Disinfectant & Cleaning agent and used as a solvent.
- Flotation agent.
- Solvent for paints & inks.

- Packed in 185kg new galvanized iron drum, 80 drums/120 drums per 20'ft/40'ft container.
- Accept OEM order.

### Precautionary statement(s)

- Avoid release to the environment.
- Wear protective gloves/ protective clothing.
- IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Do NOT induce vomiting.

### Hazard Statements

- Flammable liquid and vapour.
- Harmful if swallowed, in contact with skin or if inhaled
- May be fatal if swallowed and enters Airways.
- May cause an allergic skin reaction.
- Causes serious eye irritation.

Product	Colour	Sp. Gravity At 20°C	Refractive Index At 20°C	Terpene Alcohols
Pine Oil 60%	Colourless to Pale Yellow	0.900-0.9200	1.4750 - 1.4850	60% min